



GU100



> Type GU100



Flange expansion joint without arch

Design:	Straight or conical elastomer or multilayer expansion joint with self-sealing flanges and single or multi-part backing flanges
Installation method:	Fixes to flange at duct level
Dimensions:	For round, rectangular and oval duct cross sections
Installation length:	According to customer specification
Media temperature:	Suitable for up to 400°C
Pressure:	Up to ±0.25 bar Higher pressures on request
Movement:	For axial, lateral and angular movements Benchmarks: axial compression = approx. 0.20 x installation length axial extension = approx. 0.20 x installation length lateral displacement = approx. 0.15 x installation length In the event of axial extension and simultaneous lateral displacement, movements are reduced For large lateral movements, we recommend presetting the duct against the direction of movement

Application:

Power plants, waste incineration plants, gas turbines, cement factories, paper industry, steel industry e.g. in the exhaust pipes, in ventilators, in air ducts, in the flue gas scrubber, in filter systems



Request assembly instructions at:
www.ditec-adam.de/en/contact

Expansion joint variants

	Elastomer expansion joint	Multilayer expansion joint
Temperature:	up to 200 °C	up to 400 °C
Design:	Single-layer elastomer expansion joint fully joined with one or more fabric reinforcement inserts	Multilayer fabric expansion joint consisting of interior insulating layers, embedded sealing films and exterior pressure carrier fabrics
Material:	<p>Rubber grades: up to 100 °C: EPDM, IIR, CSM, NBR up to 180 °C: FPM up to 200 °C: Silicon (Q)</p> <p>PTFE lining: Permanently embedded on the inside at the rubber bellows in order to withstand corrosive chemical attack, available starting at \varnothing 300 mm</p> <p>Inserts: Polyamid, polyester, aramide, glass fibre, and steel mesh</p>	<p>Internal layers: PTFE glass fibre fabric laminate, glass fibre fabric, glass mat, silicate fabric</p> <p>Sealing films: PTFE film, stainless steel film</p> <p>External layer: Silicon coated glass fibre fabric PTFE-glass fibre fabric laminate</p>

Flanges

Design:	Single- or multi-part backing flanges with clearance holes
Flange norms:	According to customer specification
Materials:	Carbon steel, stainless steel
Coating:	Primed, hot-dip galvanised, special paint

Flow liners

Design:	Cylindrical, conical or telescoping flow liner (> page 360)
Materials:	Carbon steel, stainless steel
Coating:	Primed, hot-dip galvanised, special paint

Optional accessories

Fixing:	Screws Nuts Washers Disc springs
----------------	---

Cross section GU100

